



Southwire™

FIRE STOP EXPANSION FOAM

FEATURES

- In fire conditions, the pads expand to form an intumescent char that encloses the electrical box and seals off any openings that may allow the spread of flame, smoke, and toxic gases
- Putty Pad is tested to ASTM-E90, has a STC Rating of 49, and an intumescent activation of 220° Fahrenheit

APPLICATIONS

- Fire stop caulk is a low cost noncombustible material that is used to fill the space around wires, pipes, ducts and other mechanical items penetrating steel and wood framed residential construction
- Fire stop caulk fulfills fire blocking requirements for resuming the integrity of non-rated penetrations through ceiling and floor openings

CERTIFICATIONS

- UL Listed



FSFOM

PART #	DESCRIPTION	MASTER QTY.
FSFOM	12 OZ. POLYURETHANE, FIREBLOCKING FOAM SEALANT, EASY I.D. ORANGE COLOR, EVALUATED PER UL ER 38112-01, TYPE V RESIDENTIAL FIREBLOCK. FIVE MINS. TACK-FREE, ONE HOUR TO TRIM. FULL CURE 12 - 24 HOURS	1

Rev. 1, 3/24



1-855-798-6657 | SOUTHWIRE.COM

©2024 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.