



# Southwire™

## FLEXIBLE ALUMINUM CONDUIT REELS

### FEATURES

- Corrosion resistant and crush resistant
- Lightweight, easy to cut
- Smooth interior for easy wire pull through
- Easy to follow contours
- 3/8"–4" available in coils

### APPLICATION

- For use as an electrical raceway in close quarters requiring extra flexibility; one-third the weight of steel
- For use with Topaz UL listed connectors 3-1/2" thru 4" HWA

### STANDARD MATERIAL

- Aluminum alloy construction, with tempered alloy for maximum strength

### CERTIFICATIONS

- UL



4301R

PART #	SIZE	FEET/ REEL	MASTER QTY.	WEIGHT/ CASE (LBS.)	INSIDE DIAMETER		OUTSIDE DIAMETER	
					MIN.	MAX.	MIN.	MAX.
4300R	3/8"	1000'	1000	84	.374"	.392"	.559"	.609"
4301R	1/2"	1000'	1000	118	.625"	.644"	.859"	.92"
4302R	3/4"	500'	500	76	.811"	.835"	1.044"	1.105"
4303R	1"	300'	300	74	1"	1.04"	1.30"	1.379"
4304R	1-1/4"	200'	200	64	1.25"	1.30"	1.55"	1.629"
4305R	1-1/2"	100'	100	41	1.50"	1.573"	1.85"	1.95"
4306R	2"	100'	100	55	2"	2.079"	2.35"	2.45"

Rev. 0, 02/23

**BUILT FOR DURABILITY.  
BUILT FOR RELIABILITY.  
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.  
\*Registered Trademark & ™Trademark of Southwire Company, LLC.