



Southwire[®]
 WE DELIVER POWER... RESPONSIBLY*

PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1 Overlook Point, Suite 265
 Lincolnshire, IL 60069
 USA

PART NUMBER: 988421
DESCRIPTION: RG-214/U COAXIAL CABLE PER MIL-DTL-17 SWEPT TO 400 MHz
RATING: Mil-DTL-17 Qualified Products List (QPL)

Construction Parameters:

		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	12.5 AWG (7/.030) Silver Coated Copper		0.089
Dielectric:	Solid Polyethylene color natural	0.098	0.285
1 st Shielding:	96% Silver Coated Copper Braid		0.313
2 nd Shielding:	98% Silver Coated Copper Braid		0.341
Jacket:	PVC (Non-Contaminating Vinyl)	0.042	0.425

Electrical Properties:

	<u>VALUE*</u>
Conductor Resistance (Max./100 ft)	0.17
Impedance (ohms):	50
Capacitance (Max. pF/ft):	32.2
Velocity of Propagation (%):	66
Attenuation (Max. db/100 ft):	
50 MHz	1.7
400 MHz	5.5
3000 MHz	28
11000 MHz	60
SRL (Max db/100 ft):	
1.0 GHz	20
3.0 GHz	19
5.0 GHz	18
11.0 GHz	17

Cable Cross-Section:

(NOT TO SCALE)



Miscellaneous Information:

Jacket Color: Black
 Jacket Print (White): {SQFTG} SOUTHWIRE@ JAN 988421 M17/75-RG214 MIL-DTL
 17 8A7P7 {LOT#}
 Ink Jet Print (Blue): XXXXXX (Date Code)

Applicable MIL-DTL-17: M17/75F-RG214
 Approximate Weight (lb/1000 ft): 138

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.