

Job Name/Title:_____Catalog Number_____

Contractor:_____Notes:_____Notes:_____Notes:_____Notes:_____Notes:_____Notes:___Notes:___Notes:___Notes:___Notes:___Notes:___Notes:____Notes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:___NOtes:__NO

LED Green Exit and Emergency Combo



Single or Double Face in One Unit

Topaz's line of emergency exit and lighting combo units offer safety and security in an easy to install design. Emergency units are OSHA compliant and contain long lasting Ni-Cad battery backup for essential illumination during a power outage.

FEATURES

- 120/277V dual voltage operation
- Green EXIT letters and two fully adjustable LED lamp heads
- High-impact, 5VA flame retardant thermoplastic ABS housing
- Ceiling, wall, or side mounting capability (canopy included)
- Test switch and AC supply indicator
- Removeable knockout chevron directional arrows
- Battery backup with accessible test button for 90 minutes of illumination during a power outage
- Suitable for damp locatons
- Meets NFPA 70, NFPA 101, UL924, NEC and OSHA standards

APPLICATIONS

• Emergency lighting for office, industrial, retail and other public spaces





GENERAL SPECIFICATIONS

Contractor:___

Notes:

LED Green Exit and Emergency Combo

Input Voltage: 120/277V (dual voltage) Frequency: 50/60 Hz CRI: N/A **Dimmability:** No Avg. Rated Life: 500 uses Wet / Damp / Dry Location: Damp <EXIT> **Construction:** Thermoplastic Recharge time: 24 hrs Runtime: >/= 90 minutes Unit Weight: 4.05 lbs Battery Backup: Ni-Cad 3.6V 1,200mA Ambient Operating Temperature: 50°F to 104°F Energy Used in Maintenance Mode: 3.5W Battery backup, push to test button

Mounting accessories included

Track and swivel for full range adjustability AC supply indicator LED light

> Blank cover included for single face conversion

8.

SPECIFICATIONS / ORDER INFO

Catalog Number	Order Code	UPC	Mounting	Watts	Lumens	Lumens Per Watt	Dimensions	Pk-Qty
ESC/LED/GW	75141	751338034662	Wall, side or ceiling	1 watt per head	100 per head	100	13" x 2.4" x 8.3"	4-PK

NOMENCLATURE

Example: ESC/LED/GW

ESC=Exit Sign and Emergency Combo / LED=LED / GW=Green Letters, White Housing

©2019 Topaz Lighting Corp.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers. Visit www.topaz-usa.com for up-to-date dimmer compatibility information. Specifications subject to change without notice.