

SIGNA-WAVE™ - 195 SERIES Flexible Communications Cable

Material

Part Number 986195 987195 985195 Designation Standard Outdoor Watertight c(ETL)us - CMR FT4 Jacket Polyethylene Flooded-Polyethylene Riser Rated PVC

Minimum Bend Radius

Installation Temperature

Operating Temperature

Storage Temperature

1000' Stock Part Code 986195-06-08 987195-06-08 985195-06-08

Diameter

0.50"

-94[°]F to 185[°]F

-40^oF to 185^oF

-40[°]F to 185[°]F

Construction Specifications:

Inner conductor Dielectric

Outer Conductor

Jacket

Solid Copper0.037" Nom.Foamed Polyethylene0.110" Nom.Bonded Aluminum Foil + Tinned0.139" Nom.Copper Braid0.139" Nom.UV Resistant Black Polyethylene0.195" Nom.

Mechanical & Envionmental Properties:

Electrical Properties:

24.3 pF/ft
50 Ohms
80%
7.60 (Ω/1000ft)
4.90 (Ω/1000ft)
90 dB
3,000 VAC
41 GHz
2.5 kW
1,000 VDC

Attenuation & Average Power (68^oF):

Frequency (MHz)	Typical Attenuation (dB/100ft)	Average Power (kW)
30	2.00	0.89
50	2.60	0.68
150	4.40	0.39
220	5.40	0.32
450	7.80	0.22
900	11.10	0.15
1500	14.50	0.12
1800	16.00	0.11
2000	16.90	0.10
2500	19.00	0.09
5800	29.90	0.06



This product complies with European Directive (EU) 2015/863 - RoHS 3

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

On special orders, the customer must accept all factory lengths and +/- 10% of the order quantity

Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2019 Southwire Company, LLC. All Rights Reserved

Specification Issue Date: August 28, 2008

