

## 3/C CU 5KV Type SHD-GC RHINOSHIELD™ CPE Mining Cable 90°C

Flexible Copper conductors, EPR 100% Insulation Level, Cu/Nylon Braid Shield, Extra Heavy Duty Two Layer Chlorinated Polyethylene (CPE) Jacket with Optional Reflective Stripes



Image not to scale. See Table 1 for dimensions.

### CONSTRUCTION:

1. **Conductor:** Tin coated, soft drawn, annealed, flexible, rope-lay stranded copper per ASTM B33/B172
2. **Separator Tape:** Semi-conducting tape applied between the conductor and insulation to facilitate stripping
3. **Conductor Shield:** Semi-conducting cross-linked copolymer
4. **Insulation:** Ethylene Propylene Rubber (EPR) 100% Insulation Level
5. **Shield Separator:** Semi-conducting SBR tape applied to the phase insulation with a 50% overlap, adhesive side up
6. **Braid Shield:** Tin coated, soft drawn, annealed, copper braid shield (60% minimum coverage), combined with color coded nylon (black, white, red) with a 40% maximum coverage
7. **Ground Check Conductor:** Tin coated, soft drawn, annealed, rope stranded, flexible lay copper per ASTM B33/B172 with high strength yellow polypropylene insulation
8. **Ground Conductors:** Two uninsulated, tin coated, soft drawn, annealed, rope stranded, flexible lay copper per ASTM B33/B172
9. **Tape:** SBR tape applied over the cabled core for improved mechanical integrity and ease of stripping
10. **Inner Jacket:** Black, mold cured, extra heavy-duty modified integral fill, flame resistant, thermosetting Chlorinated Polyethylene (CPE)
11. **Reinforcement:** Reinforcing twine applied between the two jacket layers
12. **Outer Jacket:** Black, mold cured, extra heavy-duty, flame resistant, thermosetting Chlorinated Polyethylene (CPE). Alternate jacket colors available
13. **Reflective Stripe:** Highly visible reflective stripe embedded into the outer jacket to increase safety and help prevent cable run-over (optional, contact your sales representative for part number)

### APPLICATIONS AND FEATURES:

RHINOSHIELD™ Type SHD-GC is a heavy-duty trailing cable where flexibility and maximum protection is required. For use with mobile, reeling, or stationary mining equipment, continuous mining machines, longwall mining systems, and blast hole drillers. It is also an excellent choice for shovels, draglines, dredges, cranes and marine shore-to-ship power supplies, and anytime extra-durable, flexible cable is required. Suitable for continuous submersion in water. Ground check conductor provides fail-safe ground monitoring. Embossed print legend for easy cable identification. Cold Bend and Impact Tested to -50°C.

### SPECIFICATIONS:

- ASTM B33 Standard Specification for Tin-Coated Soft or Annealed Copper Wire
- ASTM B172 Standard Specification for Rope-Lay-Stranded Copper Conductors Having Bunch-Stranded Copper Conductors



Southwire

**CABLETECH  
SUPPORT™**

Services

- ICEA S-75-381 Portable and Power Feeder Cables for Use in Mines
- MSHA Approved

## SAMPLE PRINT LEGEND:

SOUTHWIRE (R) RHINO™ BRAND CABLE # AWG CU 3/C EPR TYPE SHD-GC 5000V -50°C 90°C P-07-KA140005 MSHA

**Table 1 – Weights and Measurements**

Stock Number	Cond. Size	Cond. Number	Cond. Strands	Diameter Over Conductor	Insul. Thickness	Diameter Over Insulation	Ground Size	Ground Strands	Ground Check Size	Ground Check Strands	Ground Check Insulation Thickness	Jacket Thickness	Approx. OD	Approx. Weight
	AWG/Kcmil	No.	No.	inch	mil	inch	AWG	No.	AWG	No.	mil	mil	inch	lb/1000ft
571484	6	3	133	0.21	110	0.496	10	104	8	168	45	185	1.56	1480
589075	4	3	259	0.256	110	0.542	8	168	8	168	45	185	1.68	1830
TBA	3	3	259	0.285	110	0.571	7	49	8	168	45	205	1.78	2100
649553	2	3	308	0.32	110	0.588	6	133	8	168	60	120	1.87	2624
587171	2	3	308	0.32	110	0.606	6	133	8	168	45	205	1.87	2400
TBA	1	3	385	0.355	110	0.641	5	133	8	168	45	205	1.95	2730
585945	1/0	3	273	0.385	110	0.671	4	259	8	168	45	220	2.08	3230
588906	2/0	3	324	0.42	110	0.706	3	259	8	168	45	220	2.20	3780
643531	3/0	3	418	0.506	110	0.792	2	308	8	168	45	235	2.36	4460
588801	4/0	3	532	0.577	110	0.863	1	385	8	168	45	235	2.50	5230
TBA	250	3	608	0.61	120	0.916	1/0	273	6	133	60	250	2.69	6190
TBA	300	3	735	0.680	120	1.043	1/0	273	6	133	60	250	2.81	6790
589188	350	3	855	0.72	120	1.026	2/0	324	6	133	60	265	2.95	7900
TBA	500	3	1221	0.9	120	1.206	4/0	532	6	133	60	280	3.31	10530

All dimensions are nominal and subject to normal manufacturing tolerances

◊ Cable marked with this symbol is a standard stock item



**Southwire**



Services

**Table 2 – Electrical and Engineering Data**

Stock Number	Cond. Size	Cond. Number	DC Resistance @ 25°C	AC Resistance @ 90°C	Capacitive Reactance	Inductive Reactance	Working Tension	Min Bending Radius	Allowable Ampacity In Air 90°C†
	AWG/ Kcmil	No.	Ω/1000ft	Ω/1000ft	MΩ*1000ft	MΩ/1000ft	lb	inch	Amp
571484	6	3	0.421	0.526	0.046	0.041	179.000	9.4	93
589075	4	3	0.267	0.334	0.040	0.039	285.000	10.1	122
TBA	3	3	0.212	0.265	0.038	0.038	360.000	10.7	140
649553	2	3	0.168	0.210	0.034	0.036	454.000	11.2	159
587171	2	3	0.168	0.210	0.034	0.036	454.000	11.2	159
TBA	1	3	0.133	0.166	0.032	0.035	572.000	11.7	184
585945	1/0	3	0.111	0.139	0.030	0.034	722.000	12.5	211
588906	2/0	3	0.085	0.106	0.028	0.034	910.000	13.2	243
643531	3/0	3	0.067	0.084	0.024	0.032	1147.000	14.2	279
588801	4/0	3	0.053	0.066	0.022	0.031	1446.000	15	321
TBA	250	3	0.045	0.056	0.022	0.031	1709.000	16.1	355
TBA	300	3	0.037	0.046	0.019	0.030	2051.000	16.9	398
589188	350	3	0.032	0.040	0.019	0.030	2393.000	17.7	435
TBA	500	3	0.023	0.029	0.016	0.028	3418.000	19.9	536

† Ampacity based on ICEA S-75-381 Table H-1 and is for a single isolated cable in air operated with an open-circuited shield at an ambient temperature of 40°C and a conductor temperature of 90°C

