

SNAP-IN CONNECTORS

90° - SQUEEZE TYPE - ZINC

FEATURES

- Easy to install
- Labor savings by simply snap the fitting into the knockout hole
- Snap-In design
- Squeeze type
- Not suitable for aluminum jacketed cables or aluminum flexible metal conduit
- Wide variety of cables

APPLICATION

- · Indoor use only
- In a dry location
- Use to connect steel to a steel outlet box or other metal enclosure

STANDARD MATERIAL

· Zinc die cast

CERTIFICATIONS

• cULus





100STSW

101STSW



PART #	SIZE	ко	INNER QTY.	MASTER QTY.	WEIGHT/CASE (LBS.)	HEIGHT	WIDTH	LENGTH
100STSW	3/8"	1/2"	25	250	2.3	1.27"	1.35"	1.87"
101STSW	1/2"	1/2"	25	250	3.1	1.55"	1.69"	2.25"

Rev. 0, 01/25



SNAP-IN CONNECTORS

90° - SQUEEZE TYPE - ZINC

APPROVED CABLES

PART #	SIZE	КО	CABLE TYPE	CONDUIT, SIZE/ CABLE, AWG	CABLE DIAMETER RANGE (IN)	
100STSW	3/8	1/2	AC CABLE, ALUMINUM	14/2 – 10/3	0.445 - 0.610	
			AC CABLE, STEEL	14/2 – 10/3	0.451 - 0.593	
			METAL CLAD CABLE, MCI-A, STEEL	14/2 - 10/3	0.451 - 0.593	
			METAL CLAD CABLE, MCI-A, ALUMINUM	14/2 – 10/3	0.439 - 0.58	
			FMC, STEEL	3/8"	0.56 - 0.61	
			FMC, ALUMINUM	3/8"	0.56 - 0.61	
			RWFMC, STEEL	3/8"	0.56 - 0.61	
			RWFMC, ALUMINUM	3/8"	0.56 - 0.61	
			METAL CLAD CABLE, MCC, ALUMINUM	14/2 - 10/3	0.451 - 0.593	
101STSW	1/2	1/2	AC CABLE, ALUMINUM	14/2 – 10/3	0.445 - 0.610	
			AC CABLE, STEEL	14/2 – 10/3	0.451 - 0.593	
			METAL CLAD CABLE, MCI-A, STEEL	14/2 - 10/3	0.451 - 0.593	
			METAL CLAD CABLE, MCI-A, ALUMINUM	14/2 – 10/3	0.439 - 0.58	
			FMC, STEEL	3/8"	0.56 - 0.61	
			FMC, ALUMINUM	3/8"	0.56 - 0.61	
			RWFMC, STEEL	3/8"	0.56 - 0.61	
			RWFMC, ALUMINUM	3/8"	0.56 - 0.61	
			METAL CLAD CABLE, MCC, ALUMINUM	14/2 – 10/3	0.451 - 0.593	