

# BRAKE CABLE

TRAILER CABLE/BRAKE CABLE



## APPLICATIONS Suitable for use as follows:

- For use as a general purpose low tension primary wire in automotive circuits where more than one conductor, color coding and flat configuration are required

## CONSTRUCTION

- Southwire's Brake Cable is manufactured using stranded bare or tinned copper conductors with individual PVC insulation and PVC Jacket

## WEIGHTS, MEASUREMENTS AND PACKAGING

NO. OF COND.	SIZE AWG	NUMBER OF STRANDS	INSULATION THICKNESS		NOMINAL OVERALL DIAMETER		NET WEIGHT	
			mm	inches	mm	inches	kg/km	lbs/Mft
2	18	16	.41	.016	6.02	.237	41.17	27.67
4	18	16	.41	.016	9.45	.372	60.61	40.73
2	16	19	.81	.032	7.98	.314	61.49	41.32
3	16	19	.58	.023	9.65	.38	69.27	46.56
4	16	19	.58	.023	13.34	.525	92.98	62.48
2	14	19	.58	.023	7.7	.303	70.53	47.4
3	14	19	.58	.023	10.67	.42	99.64	66.96
4	14	19	.58	.023	12.09	.476	108.04	72.61
3	12	19	.69	.027	12.95	.51	152.56	102.53
2	12	19	.66	.026	8.81	.347	103.12	69.3

Stranded Bare or Tinned  
Copper Conductors

60°C, 105°C, 50 Volts