



# Southwire™

## BEAM/PURLIN

# BEAM CLAMP, REVERSIBLE MALLEABLE IRON

### APPLICATION

Reversible beam clamps are used when drop rod length needs to be adjusted to accommodate the field installation finished height.

### FEATURES

Through-hole in beam clamps allows drop rod length adjustment  
Hardened cup point set screws come with jam nuts to prevent vibratory loosening in industrial settings

### MATERIAL/FINISH

Malleable iron/Unfinished (black)

### CERTIFICATIONS

UL Listed or cULus listed



3000037PLTZ



PART #	JAW OPENING	ROD SIZE	STATIC LOAD (LBS.)		BOX QTY.
			TOP MOUNT	BOTTOM MOUNT	
3000037PLTZ**	3/4"	3/8"	300	---	100
MFC-5811*	1-3/8"	5/8" - 11	750	400	25
MFC-3410*	1-3/8"	3/4" - 10	1000	600	25

\* UL listed | \*\* cULus listed

Rev. 0, 03/23

**BUILT FOR DURABILITY.  
BUILT FOR RELIABILITY.  
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.  
\*Registered Trademark & ™Trademark of Southwire Company, LLC.